

CERTIFICATE OF CONFORMITY

Certificate No.: 2016-07-18-4787391584-2

Issue Date: 2016-07-18



Product: Electronic Control Gear for LED modules

Applicant: SHANGHAI MOONS' AUTOMATION CONTROL CO LTD
BLDG 29, 4TH FL, CAOHEJING HI-TECH PARK, 69 GUIQING
RD, SHANGHAI, 200233, CHINA

Manufacturer: SHANGHAI MOONS' AUTOMATION CONTROL CO LTD
BLDG 29, 4TH FL, CAOHEJING HI-TECH PARK, 69 GUIQING
RD, SHANGHAI, 200233, CHINA

Factory: SHANGHAI MOONS' AUTOMATION CONTROL CO LTD
168 MING JIA RD, MIN-HANG DISTRICT, SHANGHAI,
201107, CHINA

Model/Type ref.: MU100M080AQxy

Rating: 120-277 V~, 50/60 Hz, 1.35 A, 135 W, tc 90°C,

Class I, IP67, symbol



Standards: EN 61347-2-13: 2014;

EN 61347-1: 2008+A1:2011+A2:2013

UL-CCIC has determined that the samples tested conform with the requirements of the above mentioned standards

The Member States of the EU shall presume compliance with the provision of the Low Voltage Directive (LVD) 2014/35/EU of 26 February 2014, the rules for CE conformity marking of the product within the LVD, when a Declaration of Conformity with the LVD has been completed and the additional requirements of Annex IV regarding internal production control and the presence of technical documentation, are complied with.

This Statement is only valid for products, which are identical to the tested products, and manufactured at the above mentioned production site. This document contains 1 page.




UL-CCIC Company Limited


2, Chengwan Road, Suzhou Industrial Park,
Suzhou, 215122, China
Tel: +86 512 6808 6400
Fax: +86 512 6808 4099

A handwritten signature in black ink, appearing to read 'Jackie Xu'.

Jackie Xu
Engineering Manager

Appendix:

Series No. (*)	Input	Output Voltage (V dc)	Output Current (mA dc)	Max output Voltage (V dc)	Max output Power (W)
MU100M080AQxy	120-277 V~, 50/60 Hz, 1.35 A, 135 W, tc 90°C, Class I, IP67, symbol 	75-189	530-800	250	100
MU100M105AQxy		57-150	450-1050	200	100
MU100M150AQxy		40-100	1000-1500	130	100

Series No. (*)	Input	Output Voltage (V dc)	Output Current (mA dc)	Max output Voltage (V dc)	Max output Power (W)
MU100M080AQx/ DCy	120-277 V~, 50/60 Hz or 170-300 V dc 1.35 A 135 W, Class I, IP67 tc 90°C symbol 	75-189	530-800	250	100
MU100M105AQx/ DCy		57-150	450-1050	200	100
MU100M150AQx/ DCy		40-100	1000-1500	130	100

(*)Note: The variant "x" "y" in model name to indicate different features noted as below:

When "/DC" follows "AQ", "/DC" is changed as "_DC"

x	Function
_0-10V	0-10V dimming function and interface
_CP	With constant power control
Blank	Without dimming board
y	Function
/C	With dimming connector
Blank	With dimming wire or null

CERTIFICATE OF CONFORMITY

Certificate No.: 2016-07-18-4787391584-6

Issue Date: 2016-07-18




Product: Electronic Control Gear for LED modules

Applicant: SHANGHAI MOONS' AUTOMATION CONTROL CO LTD
BLDG 29, 4TH FL, CAOHEJING HI-TECH PARK, 69 GUIQING
RD, SHANGHAI, 200233, CHINA

Manufacturer: SHANGHAI MOONS' AUTOMATION CONTROL CO LTD
BLDG 29, 4TH FL, CAOHEJING HI-TECH PARK, 69 GUIQING
RD, SHANGHAI, 200233, CHINA

Factory: SHANGHAI MOONS' AUTOMATION CONTROL CO LTD
168 MING JIA RD, MIN-HANG DISTRICT, SHANGHAI,
201107, CHINA

Model/Type ref.: MU100M080AQxy

Rating: 120-277 V~, 50/60 Hz, 1.35 A, 135 W, tc 90°C, 

Standards: EN 61347-2-13: 2014;
EN 61347-1: 2008+A1:2011+A2:2013

UL-CCIC has determined that the samples tested conform with the requirements of the above mentioned standards

The Member States of the EU shall presume compliance with the provision of the Low Voltage Directive (LVD) 2014/35/EU of 26 February 2014, the rules for CE conformity marking of the product within the LVD, when a Declaration of Conformity with the LVD has been completed and the additional requirements of Annex IV regarding internal production control and the presence of technical documentation, are complied with.

This Statement is only valid for products, which are identical to the tested products, and manufactured at the above mentioned production site. This document contains 1 page.




UL-CCIC Company Limited


2, Chengwan Road, Suzhou Industrial Park,
Suzhou, 215122, China
Tel: +86 512 6808 6400
Fax: +86 512 6808 4099

A handwritten signature in black ink, appearing to read 'Jackie Xu'.

Jackie Xu
Engineering Manager

Appendix:

Series No. (*)	Input	Output Voltage (V dc)	Output Current (mA dc)	Max output Voltage (V dc)	Max output Power (W)
MU100M080AQxy	120-277 V~, 50/60 Hz, 1.35 A, 135 W, tc 90°C, 	75-189	530-800	250	100
MU100M105AQxy		57-150	450-1050	200	100
MU100M150AQxy		40-100	1000-1500	130	100

Series No. (*)	Input	Output Voltage (V dc)	Output Current (mA dc)	Max output Voltage (V dc)	Max output Power (W)
MU100M080AQx/D Cy	120-277 V~, 50/60 Hz or 170-300 V dc 1.35 A 135 W, tc 90°C, 	75-189	530-800	250	100
MU100M105AQx/D Cy		57-150	450-1050	200	100
MU100M150AQx/D Cy		40-100	1000-1500	130	100

(*)Note: The variant "x" "y" in model name to indicate different features noted as below:
When "/DC" follows "AQ", "/DC" is changed as "_DC"

x	Function
_0-10V	0-10V dimming function and interface
_CP	With constant power control
Blank	Without dimming board
y	Function
/C	With dimming connector
Blank	With dimming wire or null