

CERTIFICATE OF CONFORMITY

Certificate No.: 2016-04-21-4787174760.2.1

Issue Date: 2016-04-21



Product: LED Control Gear

Applicant: SHANGHAI MOONS' AUTOMATION CONTROL CO LTD BLDG
29, 4TH FL, CAOHEJING HI-TECH PARK, 69 GUIQING RD,
SHANGHAI, 200233, CHINA

Manufacturer: SHANGHAI MOONS' AUTOMATION CONTROL CO LTD BLDG
29, 4TH FL, CAOHEJING HI-TECH PARK, 69 GUIQING RD,
SHANGHAI, 200233, CHINA

Factory: SHANGHAI MOONS' AUTOMATION CONTROL CO LTD
168 MING JIA RD, MIN-HANG DISTRICT, SHANGHAI, 201107,
CHINA

Model/Type ref.: See appendix page

Rating: See appendix page

Standard(s): EN 61347-2-13:2014; EN 61347-1:
2008+A1:2011+A2:2013

Report no: 4787174760.2.1-1; 4787174760.2.1-2

UL-CCIC has determined that the sample(s) tested conform with the requirements of the above mentioned standard(s)

The Member States of the EU shall presume compliance with the provision of the Low Voltage Directive (LVD) 2014/35/EU of 26 February 2014, the rules for CE conformity marking of the product within the LVD, when a Declaration of Conformity with the LVD has been completed and the additional requirements of Annex IV regarding internal production control and the presence of technical documentation, are complied with.

This Statement is only valid for products, which are identical to the tested products, and manufactured at the above mentioned production site. This document contains 1 page.




UL-CCIC Company Limited


2, Chengwan Road, Suzhou Industrial Park,
Suzhou, 215122, China
Tel: +86 512 6808 6400
Fax: +86 512 6808 4099

A handwritten signature in black ink, appearing to read 'Jackie Xu'.

Jackie Xu
Engineering Manager

APPENDIX PAGE

Series No. (*)	Input	Output Voltage (V dc)	Max output Current (A dc)	Max output Power (W)	Output SELV circuit
MU320H600AQx	100-240 V~, 50/60 Hz, 4.0 A max 385 W max, tc 88 °C, ta 45°C symbol 	32-80	4.0-6.0	320	SELV
MU320H800AQx		24-53.5	6.0-8.0	320	SELV
MU320H1050AQx		18-40.5	7.9-10.5	320	SELV
MU320H1330AQx		14-32	10-13.3	320	SELV

Series No. (*)	Input	Output Voltage (V dc)	Max output Current (A dc)	Max output Power (W)	Uout (V dc)
MU320H105AQx	100-240 V~, 50/60 Hz, 4.0 A max 385 W max, tc 88 °C, ta 45°C symbol 	183-457	0.7-1.05	320	500
MU320H150AQx		128-320	1.0-1.5	320	360
MU320H210AQx		91-228	1.4-2.1	320	260
MU320H300AQx		64-160	2.0-3.0	320	180
MU320H420AQx		46-114	2.8-4.2	320	130